



Chain	Pitch	Roller diameter	Inner width		Pin			Plate		Transverse pitch	Min. tensile strength	Average tensile strength	Mass per meter
	P	A	B	C	D	E	F	g	H				

norma amerykańska**Simplex**

ASA 40H-1	08AH-1	12,700	7,95	7,85	3,96	18,80	19,90	12,00	2,03		14,10	19,1	0,82
ASA 50H-1	10AH-1	15,875	10,16	9,40	5,08	22,10	23,40	15,09	2,42		22,20	30,2	1,25
ASA 60H-1	12AH-1	19,050	11,91	12,57	5,94	29,20	31,00	18,00	3,25		31,80	42,7	1,87
ASA 80H-1	16AH-1	25,400	15,88	15,75	7,92	36,20	37,70	24,00	4,00		56,70	71,4	3,10
ASA 100H-1	20AH-1	31,750	19,05	18,90	9,53	43,60	46,90	30,00	4,80		88,50	112,4	4,52
ASA 120H-1	24AH-1	38,100	22,23	25,22	11,10	53,50	57,50	35,70	5,60		127,00	160,9	6,60
ASA 140H-1	28AH-1	44,450	25,40	25,22	12,70	57,60	62,20	41,00	6,40		172,40	217,3	8,30
ASA 160H-1	32AH-1	50,800	28,58	31,55	14,27	68,20	73,00	47,80	7,20		226,80	285,8	10,30
ASA 200H-1	40AH-1	63,500	39,68	37,85	19,85	86,60	93,50	60,00	9,50		353,80	444,5	19,16

Duplex

ASA 60H-2	12AH-2	19,050	11,91	12,57	5,94	55,30	57,10	18,00	3,25	26,11	63,60	84,5	3,71
ASA 80H-2	16AH-1	25,400	15,88	15,75	7,92	68,80	70,30	24,00	4,00	32,59	113,40	145,3	6,15
ASA 100H-2	20AH-2	31,750	19,05	18,90	9,53	82,70	86,00	30,00	4,80	39,09	177,00	225,9	9,03
ASA 120H-2	24AH-2	38,100	22,23	25,22	11,10	102,40	106,40	35,70	5,60	48,87	254,00	322,7	13,13
ASA 140H-2	28AH-2	44,450	25,40	25,22	12,70	109,80	114,40	41,00	6,40	52,20	344,80	437,7	16,60
ASA 160H-2	32AH-2	50,800	28,58	31,55	14,27	130,10	134,90	47,80	7,20	61,90	453,60	571,6	20,20
ASA 200H-2	40AH-2	63,500	39,68	37,85	19,85	164,90	171,80	60,00	9,50	78,31	707,60	894,9	38,11

Triplex

ASA 60H-3	12AH-3	19,050	11,91	12,57	5,94	81,40	83,20	18,00	3,25	26,11	95,40	113,9	5,54
ASA 80H-3	16AH-3	25,400	15,88	15,75	7,92	101,40	102,90	24,00	4,00	32,59	170,10	203,5	9,42
ASA 100H-3	20AH-3	31,750	19,05	18,90	9,53	121,80	125,10	30,00	4,80	39,09	265,50	314,8	12,96
ASA 120H-3	24AH-3	38,100	22,23	25,22	11,10	151,20	155,20	35,70	5,60	48,87	381,00	444,7	19,64
ASA 140H-3	28AH-3	44,450	25,40	25,22	12,70	162,00	166,60	41,00	6,40	52,20	517,20	598,4	24,90
ASA 160H-3	32AH-3	50,800	28,58	31,55	14,27	192,00	196,80	47,80	7,20	61,90	680,40	787,3	30,10
ASA 200H-3	40AH-3	63,500	39,68	37,85	19,85	243,20	250,10	60,00	9,50	78,31	1061,40	1228,2	57,06

Chain	Pitch	Roller diameter	Inner width		Pin			Plate		Transverse pitch	Min. tensile strength	Average tensile strength	Mass per meter
	P	A	B	C	D	E	F	g	H				

norma europejska

12BHP		19,05	12,07	11,68	5,94	25,2	26,8	16	2,42		40	44,4	1,45
-------	--	-------	-------	-------	------	------	------	----	------	--	----	------	------